

IBIX 25

IBIX AUSTRALIA 

T: 1300 860 063

E: info@ibix.com.au

P O Box 645

Newport Beach NSW 2106

www.ibix.com.au

Features	
Construction	Aluminium
Pressure adjustment:	3 - 110 PSI (0.2 - 8 bar)
Abrasive Range:	20-350 Mesh (840 µm - 50 µm)
Blast hose length:	10 m
Tank capacity:	25 litres
Standard nozzle supplied:	5.5 mm (7/32") Cylindrical
ASME compliant	# 41,780
Performance:	7 m ² hour. *
Blasting Media:	Garnet, sodium bicarbonate, calcium carbonate, glass bead, plastic, walnut, corn cob etc.
Dimensions (w/out handle):	990mm (h) x 420mm x 316mm
Compressed Air Required:	1900 litres/ min (67 cfm)
Weight empty :	30 kg.
Cleaned surfaces:	Steel, aluminium, stainless steel, wood, glass, marble, concrete, masonry, stone, composite materials, tiles, etc.



Nozzle and Spare Parts Box:

- 1 cylindrical nozzle ID 3mm
- 1 cylindrical nozzle ID 7mm
- 1 Venturi nozzle ID 4mm
- 1 Venturi nozzle ID 6 mm
- 1 nozzle-holder for large nozzles
- 1 spare standard nozzle-holder



HEAVY DUTY version: Quick Connect system and tungsten carbide hosepipe, non-return valve for pressure regulator, internal funnel (V- Shape bottom) for faster empty.

H2O version - provides water-spray dust suppression .

* subject to surface, substrate, and choice of media. Higher with Ibox Helix blast gun.



Extension Hoses



Protective



Water



Helix vortex



IBIX [®]
SPECIAL CLEANING



Compressors



Dryers



Blasters



Media



ThermoPlastic Coatings